

IN THE CLAIMS

Claims 1-6 (canceled).

Claim 7 (new): A tool head fixer comprising:

a shaft including an insertion groove disposed in a front end thereof, and including a step-shaped hole disposed in the front end thereof and perpendicular to said insertion groove thereof, and including an E-shaped locking groove formed in a rear end thereof, and including a connecting shaft section protruded from the rear end of said shaft, and including a multi-angular groove disposed in a front end thereof;

an E-shaped lock engaged with said E-shaped locking groove of said shaft;

a T-shaped pressing bolt inserted inside said step-shaped hole of said shaft;

a conical reposition spring disposed on said pressing bolt;

a rotating socket pivotally disposed on said shaft, and including a connecting hole and an acentric groove formed therein,

a stopping ring disposed in said connecting hole of said rotating socket, and disposed on said shaft;

a first tool head including an insertion section for inserting into said insertion groove of said shaft, and including a fixing hole disposed in said insertion section for engaging with said pressing bolt;

said acentric groove of said rotating socket including a thicker

side for pressing said pressing bolt into said fixing hole of said insertion section of said first tool head when turning said rotating socket, to fix and hold said first tool head to said shaft, and said conical reposition spring moving said pressing bolt out of said fixing hole of said insertion section of said first tool head when turning a thinner side of said acentric groove of said rotating socket toward said pressing bolt; and

a second tool head selectively inserted into said multi-angular groove of said shaft, and including a stopping groove for selectively receiving said pressing bolt and for selectively fixing said second tool head to said shaft.

Claim 8 (new): The tool head fixer according to claim 7, wherein said pressing bolt includes a conical part for selectively engaging with said first and said second tool heads.

Claim 9 (new): The tool head fixer according to claim 7, wherein said pressing bolt includes a round head end for engaging with said rotating socket.